



## Standardised Products

		steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic	
DIN 1 (ISO 2339**)		taper pins	St	A1-A5	Br	
DIN 7 (ISO 2338**)		parallel pins	St	A1-A5	Br	
DIN 39		fixed ball handles	St		AL plastic	
DIN 84 (ISO 1207***)		slotted cheese head screws	4.8 5.8 8.8	ZP NP Cr	A1-A5	Br Cu-alloy Al plastic
DIN 85 (ISO 1580**)		slotted pan head screws	4.8 5.8 8.8	ZP NP Cr	A1-A5	Br Cu-alloy Al plastic
(ISO 7380) (ISO 14583)		slotted mushroom head screws – „slotted cup head bolts“ art. 88107 – with hexagon socket – with hexalobular socket (~TORX)	4.6 5.8 8.8 10.9 12.9	ZP NP Cr	A1-A5	Br
„ISR“		cap bolts (article 88981/88003), bolts for number plates and balcony with caps	4.8 St hard.	ZP NP	A2	Br
DIN 93		tap washers with a long tap	St	ZP	A2 A4	Br Cu Al
DIN 94 (ISO 1234*)		split pins	St	ZP	A2 A4	Br Cu Al
DIN 94		split pins assortment (article 82094)	St	ZP		
		lynch pins, spring cotter pins (→ DIN 11023/11024)	St	ZP	A2 A4	
DIN 95		slotted raised countersunk head wood screws	St	ZP HDG NP Cr Br browned enamed	A2 A4	Br Cu Cu-alloy Al
DIN 96		slotted round head wood screws				
DIN 97		slotted countersunk head wood screws				
„ISR“		theft resistant screws = half round wood screws with hexagon socket and rivet pin (article 88110)  countersunk wood screws, countersunk head wood screws up to 12 x 600 with hexalobular drive/head (~TORX) – chipboard screws (article 88098) – SPAX screws (article 88091) – SPAX special screws (article 88192-88197)	St hard. waxed	ZP HDG browned	A2 A4	
		cheese head screws with hexagon socket or hexalobular drive (~TORX), wood screws/taper screws thread (article 88312)	St hard.	ZP NP	A2 A4	
		chipboard screws/SPAX screws with cross recess type Z (article 88091-88099) – raised countersunk head – round head – countersunk head	St hard. waxed	ZP	A2	Br

\* DIN: ISO/EN identical = interchangeable  
 \*\* DIN: ISO/EN mostly interchangeable  
 \*\*\* standard conversion DIN : ISO  
 (→ Technical Information page 62)

① DIN standard withdrawn  
without replacement

Driving features:  
H = cross recess Phillips  
Z = cross recess pozidriv  
ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
-------------	--------------	-----------------	----------------------------



## Standardised Products

			steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
		SPAX screws assortment (article 88478/88479)	St hard. waxed	ZP		
DIN 97		chipboard screws/ SPAX screws, magazined (banded) chipboard screws, magazined	St	ZP	A2 A4	Br
		slotted countersunk head wood screws with inner hole	St hard. waxed	ZP		
		chipboard screws/SPAX screws countersunk head with cross recess and inner hole (article 88099)				plastic
DIN 98		caps for wood screws and chipboard screws with inner hole or with cross recess flat, half round, rustic (article 88000-88003)	St			Al plastic
DIN 99		rotatable ball handles	St		A2	
		tapered handles	St	browned		ZP/plastic plastic
DIN 123		clamping lever and tension lever	St			
DIN 124 (ISO 1051)		round rivets, nominal diameter 10-36 mm	St			
DIN 125 (→ISO 7089/ 7090*)		plain washers, type A = no chamfer, type B = with chamfer plain washers, hardened → ISO 7089/7090	St hard.	ZP HDG mechZP flZn	A2 A4	Br Cu Al plastic
DIN 125 125/127		washers assortment washers/spring lock washers assortment (article 82125/82127)	St hard.	NP Cr		
DIN 126 (ISO 7091*)		plain washers plain washers ("type 1") (article 88100)"	St	ZP HDG		
		collar washers (article 88499/88965)	St	NP Cr	A2 A4	Br Al
DIN 127 <sup>①</sup>		spring lock washers	SSt	ZP HDG flZn	1.4310 A4	bronze
		spring lock washers, double	SSt	ZP HDG		
DIN 128 <sup>①</sup>		spring washers (mandrel spring washers)	SSt	ZP HDG	1.4310 A4	bronze
DIN 137 <sup>①</sup>		spring washers type A = convex, type B = corrugated	SSt	ZP	1.4310	bronze
		TECKENTRUP lock washers for hexagon head screws and hexagon socket head cap screws (article 88123-88129)	SSt	mechZP flZn	1.4568	
		lock rings (article 88130/88131)	SSt	ZP flZn	1.4310	bronze

\* DIN: ISO/EN identical = interchangeable  
\*\* DIN: ISO/EN mostly interchangeable  
\*\*\* standard conversion DIN : ISO  
(→ Technical Information page 62)

① DIN standard withdrawn  
without replacement

Driving features:  
H = cross recess Phillips  
Z = cross recess pozidriv  
ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
-------------	--------------	-----------------	----------------------------



## Standardised Products

		steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
	SCHNORR locking washers serrated both sided, S, VS (article 88120, 88121)	St hard.	ZP mechZP flZn	A2 A4	
	NORD-LOCK washers-pair (article 88132)	St hard.	ZP flZn	A4	
DIN 186	T-head bolts with square neck	St	ZP HDG	A2 A4	
DIN 188	T-head bolts with double nip	St	ZP HDG	A2 A4	
	T-head bolts/hook bolts for profile (article 88928-88950)	4.6	ZP	A2 A4	
	T-head/hook head threaded plates (slide nuts) for profile (article 88951-88955)	St	ZP	A2 A4	
DIN 258 (ISO 8737**)	taper pins with external thread, constant taper length	St		A1 A2	
DIN 261	T-head bolts	St	ZP HDG	A2 A4	
DIN 268 DIN 271	tangential keys	St			
DIN 302 (ISO 1051)	countersunk rivets, nominal diameter 10-36 mm	St			
DIN 314 DIN 315	wing nuts, rounded or edged wings wing nuts, small version (article 88215)	St MCI	ZP NP	A2 A4	Br plastic
DIN 316 DIN 318	wing screws, rounded or edged wings	ST MCI	ZP NP	A2	Br plastic
DIN 319	ball knobs	St			plastic
DIN 338 DIN 340	twist drills with straight shank	St hard.			
DIN 388 DIN 390	hand wheels	MCI			plastic Al
DIN 404	slotted capstan screws	ST	ZP NP Cr	A1-A5	Br
DIN 417 (ISO 7435*)	slotted grub screws with full dog point	14 H	ZP	A1-A5	Br
DIN 427 (ISO 2342*)	slotted headless screws with chamfered end	14 H	ZP	A1-A5	Br
DIN 431	pipe nuts	14 H	ZP	A1-A5	Br
DIN 432 <sup>①</sup>	washers with external tap	St	ZP	A2 A4	Br Cu
DIN 433 (ISO 7092*)	washers for cheese head screws	St hard.	ZP mechZP NP Cr	A2 A4	Br

\* DIN: ISO/EN identical = interchangeable  
 \*\* DIN: ISO/EN mostly interchangeable  
 \*\*\* standard conversion DIN : ISO  
 (→ Technical Information page 62)

① DIN standard withdrawn without replacement

Driving features:  
 H = cross recess Phillips  
 Z = cross recess pozidriv  
 ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
-------------	--------------	-----------------	----------------------------



## Standardised Products

		steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
DIN 434		St	ZP HDG	A2 A4	
DIN 435		St	ZP HDG	A2 A4	
DIN 436		St	ZP HDG	A2 A4	
DIN 438 (ISO 7436*)		14 H	ZP NP	A1-A5	Br
DIN 439 (→ISO 4035/ 8675**)		04, 11 H 05, 14 H	ZP NP Cr	A1-A5	Br
DIN 440 (ISO 7094*)		St	ZP HDG		
DIN 442 DIN 443		St	ZP		
DIN 444		St	ZP	A1-A5	Br
DIN 462		St	ZP	A2 A4	Br Cu
DIN 463 <sup>①</sup>		St	ZP	A2 A4	Br Cu
DIN 464		St	ZP NP Cr	A1-A5	Br Al plastic
DIN 466		5	ZP NP Cr	A1-A5	Br Al plastic
DIN 467		5	ZP NP Cr	A1-A5	Br Al
DIN 468 DIN 469		MCI St			
DIN 470		St	ZP		
DIN 471		SSt	ZP	1.4034 1.4122 1.4310 1.4568	bronze
DIN 471		SSt			
		SSt	mechZP		
DIN 472		SSt	ZP	1.4034 1.4122 1.4310 1.4568	







\* DIN: ISO/EN identical = interchangeable  
 \*\* DIN: ISO/EN mostly interchangeable  
 \*\*\* standard conversion DIN : ISO  
 (→ Technical Information page 62)

① DIN standard withdrawn without replacement

Driving features:  
 H = cross recess Phillips  
 Z = cross recess pozidriv  
 ISR/TORX = hexalobular socket



## **Standardised Products**

DIN/ISO/EN		Standardised Products	steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
DIN 478		square head bolts with collar	5.8 8.8 10.9	ZP		
DIN 479		square head bolts with dog point	5.8 8.8 10.9	ZP		
DIN 480		square head bolts with collar, short dog point and rounded end	5.8 8.8 10.9	ZP		
DIN 508 (ISO 299*)		T-slot nuts	ST -QT			
DIN 525		studs for welding	3.6		A2 A4	
DIN 529	  	masonry bolts (anchor bolts)	3.6	ZP HDG	A2 A4	
plugs and anchors → <b>REYHER® FIXING SYSTEMS</b>						
DIN 546		slotted round nuts	St	ZP NP Cr	A1-A5	Br Al
DIN 547		double-pin nuts	St	ZP NP Cr	A1-A5	Br Al
DIN 548		capstan nuts	St	ZP NP	A1-A5	Br Al
DIN 551 (ISO 4766*)		slotted grub screws with flat point	14 H	ZP NP Cr	A1-A5	Br plastic
DIN 553 (ISO 7434*)		slotted grub screws with cone point	14 H	ZP NP Cr	A1-A5	Br plastic
		slotted spring loaded thrust pad	14 H	ZP browned	A2	
DIN 555 (ISO 4034**)		hexagon nuts	5 5-2	ZP HDG		plastic
DIN 557		square nuts	5	ZP HDG		
DIN 558 (ISO 4018**)	 	hexagon head screws, thread up to head	4.6	ZP HDG		plastic
DIN 561	 	hexagon head set screws with dog point	14 H 22 H	ZP	A1-A5	
DIN 562		square thin nuts	04 11 H	ZP NP Cr	A2 A4	Br Al
DIN 564	 	hexagon head set screws with short dog point and flat cone end	14 H 22 H	ZP	A1-A5	
DIN 571	 	hexagon head wood screws	St	ZP HDG	A2 A4	Br
		plastic sealings/caps for hexagon head, wood screws for corrugated roof panels (article 88005)	St	HDG	A2 A4	plastic

- \* DIN: ISO/EN identical = interchangeable
- \*\* DIN: ISO/EN mostly interchangeable
- \*\*\* standard conversion DIN : ISO  
(→ Technical Information page 62)

① DIN standard withdrawn without replacement

Driving features:  
H = cross recess Phillips  
Z = cross recess pozidriv  
ISR/TORX = hexalobular socket

1

steel  
coated

stainless  
steel

brass  
Cu / Al / Ti  
plastic



## Standardised Products

			steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
DIN 580		lifting eye bolts	C 15 E	ZP HDG	A2-A5	
DIN 582		lifting eye nuts	C 15 E	ZP HDG	A2-A5	
DIN 601 (ISO 4016***)		hexagon head bolts	4.6	ZP HDG		
DIN 603 (ISO 8677/ 8678**)		cup head square neck bolts	3.6 4.6 8.8	ZP HDG	A2 A4	Br plastic
DIN 603		cup head square neck bolts, thread up to square neck	St	ZP		
		slotted cup head bolts (article 88107)	4.6 5.8	ZP NP	A1-A5	Br
DIN 604		flat countersunk nib bolts	4.6 8.8	ZP		
DIN 605		flat countersunk square neck bolts	4.6	ZP		
DIN 607		cub head nib bolts	4.6	ZP		
DIN 608		flat countersunk square neck bolts with short square	4.6 8.8	ZP		
DIN 609		hexagon fit bolts with long thread	5.6 8.8		A2 A4	
DIN 610 ①		hexagon fit bolts with short thread	5.6 8.8		A2 A4	
DIN 653		knurled thumb screws, low type	St	ZP NP Cr	A1-A5	Br
DIN 660 (ISO 1051*)		round head rivets	St		A2 A4	Br Cu
DIN 661 (ISO 1051*)		countersunk head rivets	St		A2 A4	Br Cu
		mower knife rivets, half-round or countersunk	St			
		blind rivets → DIN 7337 → REYHER® FIXING SYSTEMS	St	ZP painted	A2 A4	Cu Al-alloy plastic
DIN 662 (ISO 1051*)		mushroom head rivets (sheet metal rivets)	St		A2	Br Cu
DIN 674 (ISO 1051*)		flat round head rivets	St			Br Al Cu
DIN 703 ①		adjusting rings, heavy range	St	ZP	A1-A5	
DIN 705		adjusting rings, light range	St	ZP	A1-A5	
DIN 741		clips for wire ropes	St	ZP		

\* DIN: ISO/EN identical = interchangeable  
 \*\* DIN: ISO/EN mostly interchangeable  
 \*\*\* standard conversion DIN : ISO  
 (→ Technical Information page 62)

① DIN standard withdrawn without replacement

Driving features:  
 H = cross recess Phillips  
 Z = cross recess pozidriv  
 ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
-------------	--------------	-----------------	----------------------------

DIN/ISO/EN



## Standardised Products

			steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
DIN 787 (ISO 229*)		T-slot screws	St -QT 12.9			
DIN 792		countersunk cheese head screws	4.6 5.6 8.8	ZP HDG		
DIN 797		anchor bolts	3.6	ZP HDG		
DIN 798		anchor nuts	5	ZP HDG		
DIN 835		studs, metal end = 2 d	5.6 5.8 8.8 10.9	ZP	A1-A5	Br
DIN 906		hexagon socket pipe plugs with taper thread	St	ZP	A1-A5	Br Cu-alloy
		hexagon socket pipe plugs, taper thread acc. to USA-/BS-Standard, types: NPTF, PTF, BSPT	St hard.		A1-A5	Br
DIN 908		hexagon socket pipe plugs with cylindrical thread	St	ZP	A1-A5	Br Cu-alloy
DIN 909		hexagon head pipe plugs with taper thread	St	ZP	A1-A5	Br Cu-alloy
DIN 910		hexagon head screw plugs with cylindrical thread regular type or light type	St	ZP	A1-A5	Br Cu-alloy
		screw plugs with sealing ring – with hexagon (DIN 910/DIN 5586) – with hexagon socket (DIN 908)	St	ZP		
DIN 910-2		hexagon head pipe plugs with collar and ventilation, with melted sealing (~DIN 5586)	St	ZP	A1-A5	Cu-alloy
		hexagon head pipe plugs with magnet „PM“	St	ZP		
		protective plugs, sleeves, caps for pipe ends and workpiece orifice				plastic
DIN 911 (ISO 2936*)		socket screw keys (socket wrenches) for hexagon socket (also with ball head)	St -QT	ZP NP		
		hexagon screw driver with handle	St -QT			handle = plastic
„ISR“		socket screw keys (socket wrenches) for hexalobular socket screws (~TORX)	St -QT	ZP NP		
		wrench keys assortment: rings, bags, boxes, magazines	St -QT			
DIN 912 (ISO 4762*)		hexagon socket head cap screws - with metric thread M - with metric fine pitch thread M - with inch thread UNC/UNF	8.8 10.9 12.9	ZP flZn NP Cr	A2-A5	Br
DIN 912		hexagon head cap screws with thread up to head	8.8 12.9	ZP	A2 A4	

\* DIN: ISO/EN identical = interchangeable  
\*\* DIN: ISO/EN mostly interchangeable  
\*\*\* standard conversion DIN : ISO  
(→ Technical Information page 62)

① DIN standard withdrawn without replacement

Driving features:  
H = cross recess Phillips  
Z = cross recess pozidriv  
ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
-------------	--------------	-----------------	----------------------------



## Standardised Products

			steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
„ISR“ (ISO 14579)		hexalobular socket head cap screws (~TORX)	8.8 10.9 12.9	ZP flZn	A2 A4	
		RIPP hexagon screws (article 88912)	100 12.9	ZP		
„ISR“ (ISO 7380/ 14583)		pan head/mushroom head screws – with hexagon socket – with hexalobular socket (~TORX)	4.6 8.8 10.9	ZP NP Cr	A2-A5	Br
DIN 913 (ISO 4026*)		hexagon socket set screws with flat point	45 H	ZP	A1-A5	
DIN 914 (ISO 4027*)		hexagon socket set screws with cone point	45 H	ZP	A1-A5	
DIN 915 (ISO 4028*)		hexagon socket set screws with full dog point	45 H	ZP	A1-A5	
DIN 916 (ISO 4029*)		hexagon socket set screws with cup point	45 H	ZP	A1-A5	
		spring thrust pads with hexagon socket	5.8	ZP brün	A2	
DIN 917		hexagon cap nuts, low type	6 AU 8	ZP NP Cr	A1-A5	Br Al
DIN 920		slotted small cheese head screws	5.8	ZP NP Cr	A1-A5	Br
DIN 921		slotted large cheese head screws	5.8	ZP NP Cr	A1-A5	Br
		slotted mushroom head screws (article 88107)	4.6 5.8	ZP NP	A1-A5	Br
DIN 922		slotted mushroom head screws, small head and pin	5.8	ZP NP	A1-A5	Br
DIN 923		slotted cheese head shoulder screws	5.8	ZP NP Cr	A1-A5	Br
DIN 924		slotted raised countersunk head screws with cone	5.8	ZP NP	A1-A5	Br
DIN 925		slotted countersunk head screws with cone	5.8	ZP NP	A1-A5	Br
DIN 926		threaded pins, slotted, with cone	14 H	ZP NP	A1-A5	Br
DIN 927		slotted shoulder screws	14 H	ZP NP	A1-A5	Br
DIN 928		square weld nuts	St		A1 A2	
		caged nuts (article 88109)	St	ZP		
DIN 929		hexagon weld nuts	St		A1-A5	
		weld nuts	St	ZP		

\* DIN: ISO/EN identical = interchangeable  
\*\* DIN: ISO/EN mostly interchangeable  
\*\*\* standard conversion DIN : ISO  
(→ Technical Information page 62)

① DIN standard withdrawn without replacement

Driving features:  
H = cross recess Phillips  
Z = cross recess pozidriv  
ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
-------------	--------------	-----------------	----------------------------



## Standardised Products

			steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
DIN 931 (ISO 4014***)		hexagon head bolts with shank - with metric thread M - with inch thread UNC/UNF - for container construction as per AD/TRD regulations	5.6 8.8 10.9 12.9 1.7709	ZP HDG flZn NP Cr	A2-A5 A2/A4-70 A2/A4-80	Br Cu-alloy Al plastic
DIN 933 (ISO 4017***)		hexalobular head screws/bolts (~TORX) (→ DIN 34800, 34801)	8.8 10.9	ZP	A2-A5 A2/A4-70 A2/A4-80	Br Cu-alloy Al plastic
DIN 933		hexagon head screws with thread up to head - with metric thread M - with inch thread UNC/UNF - for container construction as per AD/TRD regulations	5.6 8.8 10.9 12.9 1.7709	ZP HDG flZn NP Cr	A2-A5 A2/A4-70 A2/A4-80	Br Cu-alloy Al plastic
DIN 933		slotted hexagon head screws	5.6 8.8 10.9	ZP NP Cr	A2-A5	Br Cu-alloy Al plastic
DIN 934 (→ISO 4032, 4033** 8673/ 8674***)		locking screws, RIPP screws (TENSILOCK/DURLOK) (article 88913, 88933)	90/100 10.9 12.9	ZP	A1-A5 A2/A4-70 A2/A4-80	Br Cu-alloy Al plastic
DIN 934		hexagon nuts (article 82934, 82935)	6 8	ZP		
DIN 935		locking nuts, Ripp nuts (TENSILOCK/DURLOK) (article 88914, 88934)	10 12	ZP flZn	A1-A5	Br
DIN 936 (→ISO 4035/ 8675***)		hexagon slotted and castle nuts	6 AU 8 10	ZP NP	A1-A5	Br
DIN 936 (→ISO 4035/ 8675***)		hexagon thin nuts	04 05 17 H 22 H	ZP flZn NP Cr	A1-A5	Br Al
DIN 937 (→DIN 979)		hexagon thin slotted and castle nuts	14 H 17 H 22 H	ZP NP	A1-A5	Br
DIN 938		studs, metal end = 1 d also for container construction as per AD/TRD regulations	5.6 5.8 8.8 10.9	ZP	A1-A5 A2/A4-70	Br
DIN 939		studs, metal end = 1.25 d also for container construction as per AD/TRD regulations	5.6 5.8 8.8 10.9	ZP	A1-A5 A2/A4-70	Br
ANSI		studs, metal end = 2.5 d	5.6 8.8 ASTM AISI BS	ZP flZn PTFE	A1-A5 ASTM AISI BS	
DIN 940		threaded bolts (→ DIN 976)	5.8 8.8 10.9	ZP	A1-A5	

\* DIN: ISO/EN identical = interchangeable  
 \*\* DIN: ISO/EN mostly interchangeable  
 \*\*\* standard conversion DIN : ISO  
 (→ Technical Information page 62)

① DIN standard withdrawn without replacement

Driving features:  
 H = cross recess Phillips  
 Z = cross recess pozidriv  
 ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
-------------	--------------	-----------------	----------------------------



## Standardised Products

		steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
DIN 949-1		5.8		A1-A5	Br
DIN 949-2		8.8			
DIN 949-3		10.9			
DIN 950		GG			Al
DIN 951					
DIN 959					
DIN 960 (→ISO 8765***)		5.6 8.8 10.9 12.9	ZP	A1-A5	Br
DIN 961 (→ISO 8676***)		5.6 8.8 10.9 12.9	ZP	A2 A4	
DIN 962		additional types and finishes for screws/bolts (→ Technical Information)			
DIN 963 (ISO 2009***)		4.8 5.8 8.8	ZP NP Cr	A1-A5	Br Cu-alloy Al plastic
		4.8	ZP	A2 A4	Br
		caps for countersunk screws with inner hole (article 88000-88003)			
DIN 964 (ISO 2010***)		4.8 5.8 8.8	ZP NP Cr	A1-A5	Br Al plastic
		St	ZP NP Cr	A2 A4	Br Al
DIN 965 (ISO 7046***)		4.8 5.8 8.8	ZP NP Cr	A2 A4	Br plastic
DIN 965 „ISR“		4.8 8.8	ZP NP Cr	A2 A4	
DIN 966 (ISO 7047***)		4.8 5.8 8.8	ZP NP Cr	A2 A4	Br plastic
		St	NP Cr	A2 A4	Br Al
DIN 967		4.8 5.8 8.8	ZP NP Cr	A2 A4	Br
DIN 968		4.8 5.8 8.8	ZP NP Cr	A2 A4	Br
DIN 970 (→ ISO 4032*)		4 5 6 8 10 12	ZP HDG fZn NP Cr	A1-A5	Br Cu-alloy Al plastic Ti
DIN 971 (→ISO 8673/ 8674*)					
DIN 972 (→ISO 4034*)					

\* DIN: ISO/EN identical = interchangeable  
\*\* DIN: ISO/EN mostly interchangeable  
\*\*\* standard conversion DIN : ISO  
(→ Technical Information page 62)

① DIN standard withdrawn without replacement

Driving features:  
H = cross recess Phillips  
Z = cross recess pozidriv  
ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
-------------	--------------	-----------------	----------------------------




## Standardised Products

DIN 975



threaded rods  
 - with metric thread M  
 - with inch thread WW, UNC/UNF  
 - lengths: 1000, 2000 and 3000mm

	steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
DIN 975	4.6 4.8 5.6 5.8 8.8 10.9 ASTM	ZP HDG flZn	A1-A5 ASTM	Br plastic
DIN 975	5.8 8.8		A2 A4	
DIN 976-1	4.6 4.8 5.6 5.8 8.8 10.9 ASTM	ZP HDG flZn	A1-A5 ASTM	Br plastic
DIN 976-2				
ANSI	5.6 8.8 ASTM AISI BS	ZP HDG flZn PTFE	A1-A5 ASTM AISI BS	
DIN 977 (ISO 21670)	St			
DIN 979	04 05	ZP NP Cr	A1-A5	Br
DIN 980 (→DIN 6925***) (ISO 7042/ 7719/ 10513)	5 8 10 12	ZP NP	A1 A2 A4	Br Al
	8 10	ZP NP		
DIN 981	St		A1-A5	
	St	ZP		
DIN 982 (→DIN 6924***) (ISO 7040/ 7041/ 10512)	5 6 8 10 12	ZP NP	A1-A5	
DIN 983	SSt			
DIN 984	SSt			
DIN 985 (→DIN 6924***) (ISO 10511/ 10512)	5 6 8 10	ZP NP Br	A1-A5	Br Al

DIN 982  
(→DIN 6924\*\*\*)  
(ISO 7040/  
7041/  
10512)

prevailing torque type hexagon nuts  
 with non-metallic insert (plastic), high type

DIN 983




retaining rings with lugs for shafts  
 (retainer rings)

DIN 984



snap rings with lug,  
 retaining rings for bores

DIN 985  
(→DIN 6924\*\*\*)  
(ISO 10511/  
10512)

prevailing torque type hexagon nuts  
 with non-metallic insert (plastic), low type

\* DIN: ISO/EN identical = interchangeable  
 \*\* DIN: ISO/EN mostly interchangeable  
 \*\*\* standard conversion DIN : ISO  
 (→ Technical Information page 62)

① DIN standard withdrawn  
 without replacement

Driving features:  
 H = cross recess Phillips  
 Z = cross recess pozidriv  
 ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
-------------	--------------	-----------------	----------------------------



## Standardised Products

			steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
DIN 985		assortment of prevailing torque type hexagon nuts (article 82985)	8	ZP		
DIN 986		prevailing torque type hexagon domed cap nuts with non-metallic insert	5 6 8 10	ZP NP	A1-A5	
DIN 988		shim rings/supporting rings	St SSt		A1-A5	
DIN 1052		timber connectors, spikes one sided or two sided metal sheet/malleable cast iron	MCI St	black varnish ZP HDG flZn		
DIN 1052		washers for timber connectors	St	ZP HDG flZn	A2 A4	
DIN 1052		ABC threaded rods with wood screw thread for lateral pass and lateral pressure reinforcement for large timber components (article 88052)	St			
DIN 1142 (EN 13411)		clamps for wire ropes for end joints	MCI stirrup 6.8	ZP	A2 A4	
ISO 1207 (DIN 84)		slotted cheese head screws	4.8 5.8	ZP NP Cr Br	A1-A5	Br Cu-alloy Al plastic
ISO 1234* (→ DIN 94)		split pins	St	ZP	A2	Br Cu Al
DIN 1433-1436		bolts with or without head (→ DIN 1443/1444)	St	ZP	A1-A5	Br Al
DIN 1440 (ISO 8738**)		washers for clevis pins, product grade A	St	ZP NP	A1-A5	Br
DIN 1441		washers for clevis pins, product grade C	St	ZP NP	A1-A5	Br
DIN 1443 (ISO 2340)		clevis pins without head, type A = without pin holes type B = with pin holes	St HDG	ZP HDG	A1-A5	Br Al
		quick assembly elements for axles, shafts, bolts and pins; axle clamping rings, Duo-Clips, spring pins, KL-/SL-safety, U-Clips, Bajonett-Clips, PALNUT-Clips"	SSt mechZP flZn	ZP mechZP flZn	1.4310	
DIN 1444 (ISO 2341**)		clevis pins with head type A = without pin hole type B = with pin hole	St	ZP HDG flZn	A1-A5	Br Al
DIN 1445		clevis pins with head and cone end	St	ZP	A1-A5	Br Al
DIN 1469		grooved pins with neck	St	ZP NP	A1 A2 1.4104	Br Al plastic
DIN 1470 (ISO 8739**)		straight grooved pins with pilot end	St	ZP NP	A1 A2 1.4104	Br Al plastic

\* DIN: ISO/EN identical = interchangeable  
 \*\* DIN: ISO/EN mostly interchangeable  
 \*\*\* standard conversion DIN : ISO  
 (→ Technical Information page 62)

① DIN standard withdrawn without replacement

Driving features:  
 H = cross recess Phillips  
 Z = cross recess pozidriv  
 ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
-------------	--------------	-----------------	----------------------------



## Standardised Products

		steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic	
DIN 1471 (ISO 8744**)		grooved pins, full-length taper grooved	St	ZP NP	A1 A2 1.4104	Br Al plastic
DIN 1472 (ISO 8745**)		grooved pins, half length taper grooved	St	ZP NP	A1 A2 1.4104	Br Al plastic
DIN 1473 (ISO 8740**)		grooved pins, full length parallel grooved	St	ZP NP	A1 A2 1.4104	Br Al plastic
DIN 1474 (ISO 8741**)		grooved pins, half length reverse grooved	St	ZP NP	A1 A2 1.4104	Br Al plastic
DIN 1475 (ISO 8742/8743)		grooved pins, third length centre grooved	St	ZP NP	A1 A2 1.4104	Br Al plastic
DIN 1476 (ISO 8746*)		grooved pins with round head	St	ZP NP	A1 A2 1.4104	Br Al plastic
DIN 1477 (ISO 8747*)		grooved pins with countersunk head	St	ZP NP	A1 A2 1.4104	Br Al plastic
DIN 1478		turnbuckles made from tubes SP = turnbuckles without accessories SPAЕ = with 2 welding studs	St 35 St 50-2	ZP flZn	A2 A4	
		shroud turnbuckles	St	ZP flZn	A4	
DIN 1479		hexagon turnbuckles	St 6 AU	ZP flZn	A1-A5	Br
		coupling sleeves, - hexagonal (article 88087) - round (article 88088)	St flZn	ZP flZn	A1-A5	Br
ISO 1479* (→ DIN 7976)		hexagon head tapping screws	St case-hard.	ZP NP Cr	A2 A4	
DIN 1480		turnbuckles, forged, SP = turnbuckles without accessories SP-AE = with 2 welding studs SP-RR = with 2 eye bolts SP-RH = with eye bolts and hook bolts SP-HH = with 2 hook bolts SP-BS = with 2 flat leaf screws	3.6	ZP flZn	A4	
DIN 1481 (ISO 8752**)		spring type straight pins, heavy duty	SSt		1.4310	
		spring type straight pins, tooth slotted („CONNEX“)	SSt		1.4310	
DIN 1481		spring type straight pins assortment (article 82481)	SSt			
ISO 1481 (DIN 7971**)		slotted cheese head taper screws type C = cone end, type F = full dog point type R = round cone end	St case-hard.	ZP NP Cr	A2 A4	
ISO 1482 (DIN 7972***)		slotted countersunk taper screws	St case-hard.	ZP NP Cr	A2 A4	

\* DIN: ISO/EN identical = interchangeable  
 \*\* DIN: ISO/EN mostly interchangeable  
 \*\*\* standard conversion DIN : ISO  
 (→ Technical Information page 62)

① DIN standard withdrawn without replacement

Driving features:  
 H = cross recess Phillips  
 Z = cross recess pozidriv  
 ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
-------------	--------------	-----------------	----------------------------



## Standardised Products

			steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
ISO 1483 (DIN 7973***)		slotted raised countersunk taper screws	St case-hard.	ZP NP Cr	A2 A4	
ISO 1580 (DIN 85**)		slotted pan head screws	4.8 5.8	ZP NP Cr	A1-A5	Br Cu-alloy Al plastic
DIN 1587		hexagon domed cap nuts, high type	6 AU 8	ZP NP Cr	A1-A5	Br Al plastic
DIN 1592 1593 1596 1597		pipe clips	St	ZP HDG primed	A2-A5	
		pipe clamps, pipe rack	St	ZP HDG	A2-A5	
EN 1661 (DIN 6923)		hexagon nuts with flange locking-/RIPP nuts with flange (TENSILOCK/DURLOCK) (article 88914,88934)	8 10 12	ZP flZn NP	A2 A4	
EN 1662 EN 1665 (DIN 6921) (DIN 6922)		hexagon screws with flange, light type, heavy type	8.8 10.9	ZP flZn	A2 A4	
EN 1663 EN 1666 (DIN 6926**)		prevailing torque type hexagon nuts with flange and non-metallic insert	8 10 12	ZP flZn NP	A2 A4	
EN 1664 EN 1667 (DIN 6927**)		prevailing torque type hexagon nuts with flange, all-metal, coarse thread, fine pitch thread	8 10 12	ZP flZn NP	A2 A4	
DIN 1804		slotted round nuts for hook spanner	St		A2-A5	
		locknuts with non-metallic insert GUA/GUK/GUP, FINE-U-Nut	St	ZP		
DIN 1816		round nuts with set pin holes inside	St	ZP NP Cr	A1-A5	Br
ISO 2009 (DIN 963***)		slotted countersunk screws	4.8 5.8	ZP NP Cr	A1-A5	Br Cu-alloy Al plastic
ISO 2010 (DIN 964***)		slotted raised countersunk screws	4.8 5.8	ZP NP Cr	A1-A5	Br Cu-alloy Al plastic
DIN 2093		disc springs	SSt	mechZP flZn	1.4122 1.4310 1.4568	Bronze
		TECKENTRUP conical spring washers	SSt	mechZP flZn	1.4568	
ISO 2338 (DIN 7**)		parallel pins	St		A1-A5	Br
ISO 2339 (DIN 1**)		taper pins	St		A1-A5	Br

\* DIN: ISO/EN identical = interchangeable  
 \*\* DIN: ISO/EN mostly interchangeable  
 \*\*\* standard conversion DIN : ISO  
 (→ Technical Information page 62)

① DIN standard withdrawn without replacement

Driving features:  
 H = cross recess Phillips  
 Z = cross recess pozidriv  
 ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
-------------	--------------	-----------------	----------------------------



## Standardised Products

		steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic	
ISO 2341 (DIN 1444**)		bolts with head	St	ZP HDG flZn	A1-A5	Br Al
ISO 2342* (→ DIN 427)		slotted headless screws with chamfered end	14 H	ZP	A1-A5	Br
DIN 2509		double end studs	5.6			
DIN 2510		bolts with waisted shank, with certificate EN 10204/3.2/3.1	material → DIN 267-13		material → DIN 267-13	
DIN 2510		hexagon nuts for bolts with inspection certificate EN 10204/3.1	material → DIN 267-13		material → DIN 267-13	
DIN 2510		cap nuts for bolts with certificate EN 10204/3.1	material → DIN 267-13		material → DIN 267-13	
DIN 2510		clamping sleeves for bolts with certificate EN 10204/3.1	material → DIN 267-13		material → DIN 267-13	
ANSI		threaded bolts with hexagon nuts	5.6 8.8 ASTM AISI, BS	ZP HDG flZn PTFE	A2 A4 ASTM AISI BS	
DIN 3015 3016		fastening clamps with rubber profile	St MCI	ZP HDG	1.4016 A2 A4	Al plastic
DIN 3017		hose clamps	St	ZP	1.4301 1.4436	
DIN 3090 (→ DIN 6899)		thimbles	St	ZP HDG	A4	
DIN 3220 3319		hand wheels, flat and cranked	St	ZP	1.4016 1.4301 1.4401 1.4436 1.4571	
DIN 3404		lubricating nipples, button head	St	ZP	A2 A4	Br
DIN 3405		lubricating nipples, cupped type	St	ZP	A2 A4	Br
DIN 3567		pipe clamps	St	ZP HDG	A2 A4	
		tubular clamps with noise protection inlays (DIN 4109)	St	ZP	A2 A4	
		pipe support, pipe hangers	St	ZP HDG flZn	A2 A4	
DIN 3568		clamping plates for pipe fixings	St 37	ZP flZn		
		LINDAPTER-clamping elements → <b>REYHER® FIXING SYSTEMS</b>		MCI	ZP HDG	
DIN 3570		stirrup bolts	St	ZP HDG	A2 A4	Br

\* DIN: ISO/EN identical = interchangeable  
 \*\* DIN: ISO/EN mostly interchangeable  
 \*\*\* standard conversion DIN : ISO  
 (→ Technical Information page 62)

① DIN standard withdrawn  
without replacement

Driving features:  
 H = cross recess Phillips  
 Z = cross recess pozidriv  
 ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
-------------	--------------	-----------------	----------------------------



## Standardised Products

		steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
DIN 3575		anchors with welding ends for pipe suspension	St 37	ZP	A2 A4
DIN 3670		disc hand wheels			Al
DIN 3870		cap nuts	St	ZP flZn	A1-A5
DIN 3872					Br
ISO 4014*/***(DIN 931)		hexagon head bolts with shank - also for container construction as per AD/TRD regulations	5.6 8.8 10.9 12.9 1.7709	ZP HDG flZn NP Cr	A2-A5 A2/A4-70 A2/A4-80
ISO 4015		hexagon bolts with shank-Ø ~ pitch -Ø	5.8 8.8	ZP HDG flZn	A2 A4
ISO 4016*/***(DIN 601)		hexagon head bolts with shank	3.6 4.6 4.8	ZP HDG flZn	
ISO 4017*/***(DIN 933)		hexagon head screws with thread up to head - also for container constructions as per AD/TRD regulations	5.6 8.8 10.9 12.9 1.7709	ZP HDG flZn NP Cr	A2-A5 A2/A4-70 A2/A4-80
ISO 4018*/***(DIN 558)		hexagon head screws with thread up to head	3.6 4.6 4.8	ZP HDG flZn	
ISO 4026* (→ DIN 913)		hexagon socket set screws with flat point	45 H	ZP	A1-A5
ISO 4027* (→ DIN 914)		grub screws with hexagon socket and cone end	45 H	ZP	A1-A5
ISO 4028* (→ DIN 915)		hexagon socket set screws with full dog point	45 H	ZP	A1-A5
ISO 4029* (→ DIN 916)		hexagon socket set screws with cup point	45 H	ZP	A1-A5
ISO 4027* (→ DIN 914)		hexagon socket set screws with cone point	5 5-2 6 8 10	ZP HDG flZn NP Cr browned	A1-A5 A2/A4-70 A2/A4-80
ISO 4032***(DIN 934)		hexagon nuts, ISO type 1, coarse thread, - also for container construction as per AD/TRD regulations			Br Cu-alloy Al plastic Ti
ISO 4033***(DIN 934)		hexagon nuts, ISO type 2, coarse thread	12	ZP HDG flZn	
ISO 4034*** (DIN 555)		hexagon nuts	4 5	ZP HDG flZn	
ISO 4035		hexagon thin nuts (with chamfers/without chamfers)	04 05 110 HV 30	ZP NP Cr	A1-A5
4036***/***(DIN 439/ 936)					Br
DIN 4109		tubular clamps with noise protection inlay	St	ZP	A2 A4
ISO 4762* (→ DIN 912)		hexagon socket head cap screws	8.8 10.9 12.9	ZP flZn NP	A2-A5
ISO 4766* (→ DIN 551)		slotted grub screws with flat point	14 H	ZP NP Cr	A1-A5
* DIN: ISO/EN identical = interchangeable		① DIN standard withdrawn without replacement	Driving features: H = cross recess Phillips Z = cross recess pozidriv ISR/TORX = hexalobular socket	steel plain	steel coated
** DIN: ISO/EN mostly interchangeable				stainless steel	brass Cu / Al / Ti plastic
*** standard conversion DIN : ISO (→ Technical Information page 62)					



## Standardised Products

		steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
DIN 5299		St	ZP		
DIN 5406 MB/MBL		St	ZP		
DIN 5417		SSt			
DIN 5525		St HDG	ZP HDG	A1-A5	Br Al
DIN 5526		St HDG	ZP HDG	A1-A5	Br Al
DIN 5586		St	ZP	A1-A5	
DIN 5903		4.6	ZP		
DIN 5906		St HDG flZn	ZP HDG flZn		
		MCI	ZP HDG		
DIN 5914		St	HDG		
DIN 6303		5	ZP NP Cr	A1 A2 A4	Br Al
DIN 6304		5.8	ZP		
DIN 6305		5	ZP		
DIN 6306		5.8	ZP		
DIN 6307		5	ZP		
DIN 6311		St hard.	ZP		
DIN 6319		St hard. St -QT	ZP flZn		
DIN 6324		St			plastic
DIN 6325 (ISO 8734*)		St hard.			
DIN 6330		6 AU 8 10	ZP	A1-A5	Br

\* DIN: ISO/EN identical = interchangeable  
\*\* DIN: ISO/EN mostly interchangeable  
\*\*\* standard conversion DIN : ISO  
(→ Technical Information page 62)

① DIN standard withdrawn without replacement

Driving features:  
H = cross recess Phillips  
Z = cross recess pozidriv  
ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
-------------	--------------	-----------------	----------------------------



## Standardised Products

		steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
DIN 6331		hexagon nuts with collar, with a height of 1,5 d	6 AU 8 10	ZP	A1-A5
DIN 6332		grub screws with thrust point	5.8 8.8	ZP	
DIN 6334		hexagon nuts with a height of 3 d	6 AU 8 10	ZP	A1-A5
DIN 6335		palm grips	St		Br
DIN 6336		star grips	St		plastic
DIN 6337		ball handles	St		plastic
DIN 6340		washers for clamping devices, hardened	St -QT	ZP flZn	
DIN 6378		hook bolts	8.8		
DIN 6379		studs for use with t-nuts	8.8		
DIN 6791 (ISO 1051**)		semi-tubular pan head rivets	St		Cu Br Al
DIN 6792 (ISO 1051**)		semi-tubular countersunk head rivets	St		Cu Br Al
DIN 6796 (ISO 10670**)		conical spring washers	SSt	mechZP flZn	1.4310
		TECKENTRUP conical spring washers	SSt	mechZP flZn	1.4568
DIN 6797 <sup>①</sup>		toothed lock washers type A = external teeth type I = internal teeth type V = countersunk	SSt	ZP	1.4310
		TECKENTRUP lock washers for hexagon head screws and hexagon socket cap screws (article 88123-88126)	SSt	mechZP flZn	1.4568
		TECKENTRUP lock washers with contact serrations (article 88129)	SSt	mechZP flZn	A4
		SCHNORR safety washers with serration on both sides S, VS (article 88120, 88121)	St hard.	ZP flZn	A2 A4
		lock rings (article 88130, 88131)	SSt	ZP flZn	1.4310
		NORD-LOCK washers preassembled pairs standard = normal outer diameter SP = enlarged outer diameter (article 88132)	St hard.	ZP flZn	A4
DIN 6798 <sup>②</sup>		serrated lock washers type A = external teeth type I = internal teeth type V = countersunk	SSt	ZP	1.4310 A4

\* DIN: ISO/EN identical = interchangeable  
 \*\* DIN: ISO/EN mostly interchangeable  
 \*\*\* standard conversion DIN : ISO  
 (→ Technical Information page 62)

① DIN standard withdrawn without replacement

Driving features:  
 H = cross recess Phillips  
 Z = cross recess pozidriv  
 ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
-------------	--------------	-----------------	----------------------------



## Standardised Products

		steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
		SSt	mechZP flZn	A4	
		SSt	ZP flZn	A4	bronze
DIN 6799		SSt		1.4034 1.4122	bronze
		SSt mechZP flZn	ZP mechZP flZn	1.4310	
DIN 6880		St			
DIN 6881		St		A2	
DIN 6883 (ISO 2492)				A4	
DIN 6884 (ISO 2492)		St		A2	
DIN 6885 (ISO 773/ 2491**)		St		A2	
DIN 6887 (ISO 774**)		St		A2	
DIN 6888 (ISO 3912**)		St		A2	
DIN 6899		St	ZP HDG	A2	
DIN 6900 (ISO 10644) DIN 6901 (ISO 10510)		4.8 5.8 8.8 10.9 St case-hard.	ZP NP Cr	A2	Br
		6 8 10	ZP NP Cr	A4	
DIN 6902- DIN 6908 (ISO 10669/ 10673)		St SSt	ZP NP Cr brün	A2 A4 1.4310	Br Cu-alloy bronze plastic
DIN 6911		St -QT	ZP NP		
DIN 6912		8.8 10.9	ZP flZn NP	A2 A4	Cu-alloy
DIN 6914 (→ EN 14399)		10.9 (12.9)	HDG		
HVP		10.9	HDG		
HRC (HVA)		10.9	HDG		

\* DIN: ISO/EN identical = interchangeable  
 \*\* DIN: ISO/EN mostly interchangeable  
 \*\*\* standard conversion DIN : ISO  
 (→ Technical Information page 62)

① DIN standard withdrawn without replacement

Driving features:  
 H = cross recess Phillips  
 Z = cross recess pozidriv  
 ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
-------------	--------------	-----------------	----------------------------



## Standardised Products

		steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
DIN 6915 (→EN 14399)		hexagon nuts with large wrench size for high-strength structural bolting, system HV	10 (12)	HDG	
DIN 6916 (→EN 14399)		plain chamfered washers for high-strength structural bolting, system HV	C 45 -QT	HDG	
DIN 6917		square taper washers, for friction grip bolts on I sections in steel constructions	C 45 -QT	HDG	
DIN 6918		square taper washers, for friction grip bolts on U sections in steel constructions	C 45 -QT	HDG	
DIN 6921 DIN 6922 (ISO 4162/ 8100-04) (EN 1665)		hexagon flange bolts	8.8 10.9 12.9	ZP flZn	
		hexagon flange bolts acc. to MBN 10105 (article 10105)			
		locking screws, RIPP screws (TENSILOCK/DURLOK) (article 88913, 88933)	90/100 10.9 12.9	ZP	
DIN 6923 (ISO 4161) (EN 1661)		hexagon flange nuts	8 10 12	ZP flZn	A2 A4
		hexagon flange nuts acc. to MBN 13023 (article 13023)			
		hexagon locking nuts with flange	8 10 12	ZP flZn	A2 A4
		locking nuts, RIPP nuts (TENSILOCK/DURLOK) (article 88914, 88934)	10 12	ZP flZn	A2 A4
DIN 6924 (ISO 7040**/ 10512)		prevailing torque type hexagon nuts with non-metallic insert (plastic)	5 8 10 12	ZP flZn NP Cr	
DIN 6925 (ISO 7042**/ 7719/ 10513)		prevailing torque type hexagon nuts, all-metal	5 8 10 12	ZP NP Cr	
DIN 6926 (ISO 7043/ 12125) (EN 1663, 1666)		prevailing torque type hexagon nuts with flange, non-metallic insert (plastic)	8 10 12	ZP flZn NP Cr	
DIN 6927 (ISO 7044/ 12126) (EN 1664, 1667)		prevailing torque type hexagon nuts with flange, all-metal	8 10 12	ZP flZn NP Cr	
		nuts with cavity washers	6 8 10	ZP NP Cr	A2 A4
DIN 6928 (ISO 7053/ 10509)		hexagon taper screws with collar type C = cone end type F = full dog point type R = round cone end	Stahl case-hard.	ZP NP Cr	A2 A4
ISO 7040 (→ DIN 6924)		prevailing torque type hexagon nuts with non-metallic insert (plastic)	5 8 10	ZP flZn NP Cr	A2 A4

\* DIN: ISO/EN identical = interchangeable  
 \*\* DIN: ISO/EN mostly interchangeable  
 \*\*\* standard conversion DIN : ISO  
 (→ Technical Information page 62)

① DIN standard withdrawn  
without replacement

Driving features:  
H = cross recess Phillips  
Z = cross recess pozidriv  
ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
-------------	--------------	-----------------	----------------------------



## Standardised Products

			steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
ISO 7042* (→ DIN 6925)		prevailing torque type hexagon nuts, all-metal	5 8 10 12	ZP flZn NP Cr		
ISO 7045 (DIN 7985**)		pan head screws with cross recess type H or Z	4.8	ZP NP Cr	A2 A4	Br plastic
ISO 7046-1 ISO 7046-2 (DIN 965***)		countersunk screws with cross recess type H or Z	4.8 8.8	ZP NP Cr	A2 A4	Br plastic
ISO 7047 (DIN 966***)		raised countersunk screws with cross recess type H or Z	4.8 8.8	ZP NP Cr	A2 A4	Br plastic
ISO 7049 (DIN 7981**)		pan head tapping screws with cross recess	St case-hard.	ZP NP Cr	A2 A4	
ISO 7050*** (DIN 7982)		countersunk head tapping screws with cross recess, countersunk $\angle = 90^\circ$ , with cross recess type H or Z	St case-hard.	ZP NP Cr	A2 A4	
ISO 7089* (DIN 125)		plain washers, normal series, without chamfer, product grade A	St 200 HV 300 HV	ZP flZn NP Cr	A1-A5	Br Cu Al plastic
ISO 7090* (DIN 125)		plain washers, normal series, with chamfer, product grade A	St 200 HV 300 HV	ZP flZn NP Cr	A1-A5	Br Cu Al plastic
ISO 7091* (→ DIN 126)		plain washers, normal series, product grade C	St 100 HV	ZP HDG flZn	A2 A4	
ISO 7092* (→ DIN 433)		plain washers, small series, product grade A	St 200 HV 300 HV	ZP flZn NP Cr	A1-A5	Br
ISO 7093-1 ISO 7093-2* (→ DIN 9021)		plain washers, large series, product grade A	St 200 HV 300 HV	ZP HDG flZn	A1-A5	Br Al
ISO 7094* (→ DIN 440)		plain washers, extra large series, product grade C	St 100 HV	ZP HDG flZn	A2 A4	
DIN 7331		compression rivets	St	NP BP painted		Br
DIN 7337 (ISO 15973-16585)		blind rivets (article 88401-88488) → <b>REYHER® FIXING SYSTEMS</b>	St	ZP painted	A2 A4	Al Cu Cu-alloy plastic
		special blind rivets, blind rivet nuts, setting tools and assortment boxes	St	ZP painted	A2 A4	Al Cu
DIN 7338		rivets for brake linings and clutch linings	St			
DIN 7339 DIN 7340		hollow rivets, tubular rivets	St			Br Cu Al

\* DIN: ISO/EN identical = interchangeable  
 \*\* DIN: ISO/EN mostly interchangeable  
 \*\*\* standard conversion DIN : ISO  
 (→ Technical Information page 62)

① DIN standard withdrawn without replacement

Driving features:  
 H = cross recess Phillips  
 Z = cross recess pozidriv  
 ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
-------------	--------------	-----------------	----------------------------



## Standardised Products

DIN/ISO/EN		Standardised Products	steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
DIN 7341 (ISO 1051)		rivet pins	St		A1-A5	Br
		spacers/couplings hexagonal/round (article 88086-88088)	St		A1-A5	Al Br plastic
DIN 7343 (ISO 8750/ 8751)		spring-type straight pins, coiled, standard duty	SSt		1.4310	
DIN 7344 (ISO 8748**)		spring-type straight pins, coiled, heavy duty	SSt		1.4310	
DIN 7346 (ISO 13337*)		spring-type straight pins, slotted, light duty	SSt		1.4310	
		spring-type straight pins with tooth slot, („CONNEX coiled spring pins“)	SSt		1.4310	
DIN 7349		washers for screws with heavy spring-type straight pins	St	ZP HDG NP	A2	
ISO 7379		hexagon socket head shoulder screws	10.9 12.9			
ISO 7380		hexagon socket button head screws	10.9 12.9	ZP	A2 A4	Br
		hexagon socket button head screws with flange	4.6 8.8 10.9 12.9	ZP	A2 A4	
„ISR“ (ISO 14583)		hexalobular socket button head screws (~TORX)	8.8 10.9 12.9	ZP	A2 A4	
ISO 7434* (→DIN 553)		slotted grub screws with cone point	14 H	ZP NP	A1-A5	Br
ISO 7435* (→DIN 417)		slotted grub screws with full dog point	14 H	ZP NP	A1-A5	Br
ISO 7436* (→DIN 438)		slotted grub screws with cup point	14 H	ZP NP	A1-A5	
DIN 7500		thread rolling screws for ISO metric thread type C = pan head ~type D = hexagon head with collar type E = cylinder head with hexagon socket type M = countersunk head type CE-ISR/PE = pan head, hexalobular socket	St case-hard.	ZP		
DIN 7504 (ISO 15480- 15483)		drilling screws with tapping screw thread type K = hexagon head with collar type N = pan head type P = countersunk head	St case-hard.	ZP NP		
DIN 7513		thread cutting screws type A = hexagon head type B = slotted cheese head	St case-hard.	ZP		
DIN 7516		thread cutting screws with cross recess type A = pan head type D = countersunk head type E = raised countersunk head	St case-hard.	ZP		
		cut/scrapers groove threaded bolts, self tapping screws (→ DIN 7500)	St case-hard.	ZP		
DIN 7603		sealing rings			Cu Al fibre	

- \* DIN: ISO/EN identical = interchangeable
- \*\* DIN: ISO/EN mostly interchangeable
- \*\*\* standard conversion DIN : ISO  
(→ Technical Information page 62)

- ① DIN standard withdrawn without replacement

**Driving features:**  
H = cross recess Phillips  
Z = cross recess pozidriv  
ISR/TORX = hexalobular socket

st  
pl

steel  
coated

stainless  
steel

Cu  
Al  
fibre



## Standardised Products

		steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic	
DIN 7604		hexagon head screw plugs with collar	St	ZP	A1-A5	Br Al plastic
DIN 7642 DIN 7643		hollow screws for ring type banjos	St		A1-A5	
ISO 7719		prevailing torque type hexagon nuts, ISO type 1, all-metal	5 8 10	ZP flZn NP Cr		
DIN 7964		hexagon head screws with waisted shank type A = head acc. to DIN 84 type B = head acc. to DIN 85 type C = head acc. to DIN 7985 type D1/D2 = head acc. to ISO 4014/DIN 931 type E = head acc. to DIN 912 (ISO 4762)	5.6 5.8 8.8	ZP NP	A1-A5	Br
DIN 7965		screwed inserts "RAMPA"	St	ZP	A2 A4	Br Al plastic
		tee nuts with prong (article 88108)	St	ZP		
DIN 7967 ①		self locking counter nuts	SSt	ZP HDG	1.4310	
		PAL-hatclips-nuts	SSt	ZP		
DIN 7968		hexagon fit bolts for steel structures	5.6 8.8	ZP HDG		
DIN 7969		slotted countersunk head bolts for steel structures	4.6 5.6	ZP HDG		
DIN 7971 (ISO 1481**)		slotted pan head tapping screws type C = cone end, type F = flat end, type R = rounded end	St case-hard.	ZP NP Cr	A2 A4	
DIN 7972 (ISO 1482***)		slotted countersunk head tapping screws	St case-hard.	ZP NP Cr	A2 A4	
DIN 7973 (ISO 1483***)		slotted raised countersunk head tapping screws	St case-hard.	ZP NP Cr	A2 A4	
		clip/spring nuts for tapper screw threads (→ DIN 34818)	SSt	ZP		
DIN 7971/ 7973		tapping screw assortment (article 82971, 82973)	ST case-hard.	ZP		
DIN 7976 (ISO 1479**)		hexagon head tapping screws	St case-hard.	ZP NP Cr	A2 A4	
		tapping screws for facing (article 88176, 88276) with assembled sealing washer type A = with cone end, type BZ = with full dog point	St case-hard.	ZP	A2	
		cylindrical head tapping screws with hexagon socket (article 88312)	St case-hard.	ZP NP	A2 A4	

\* DIN: ISO/EN identical = interchangeable  
 \*\* DIN: ISO/EN mostly interchangeable  
 \*\*\* standard conversion DIN : ISO  
 (→ Technical Information page 62)

① DIN standard withdrawn without replacement

Driving features:  
 H = cross recess Phillips  
 Z = cross recess pozidriv  
 ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
-------------	--------------	-----------------	----------------------------



## Standardised Products

			steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
DIN 7977 (ISO 8737*)		taper pins with external thread, constant threaded part	St		A1-A5	
DIN 7978 (ISO 8736*)		taper pins with internal thread	St		A1-A5	
DIN 7979 (ISO 8733/ 8735*)		parallel pins with internal thread	St		A1-A5	
DIN 7980 ①		spring lock washer for cheese head screws	SSt	ZP	1.4310 A4	
		TECKENTRUP lock washers „Z“ for hexagon head screws and hexagon socket head cap screws (article 88126)	SSt	mechZP flZn	1.4568	
		lock rings „VSK-Z“ (article 88131)	SSt	flZn		
DIN 7981 (ISO 7049**)		pan head tapping screws with cross recess type H or Z	St case-hard.	ZP NP Cr	A2 A4	
DIN 7981 ISR (ISO 14585)		pan head tapping screws with hexalobular socket (~TORX)	St case-hard.	ZP NP Cr	A2 A4	
DIN 7982 (ISO 7050***)		countersunk head tapping screws with cross recess type H or Z	St case-hard.	ZP NP Cr	A2 A4	
DIN 7982 "(ISR" ISO 14586)"		countersunk head tapping screws with hexalobular socket (~TORX)	St case-hard.	ZP NP Cr	A2 A4	
DIN 7983 (ISO 7051***)		raised countersunk head tapping screws with cross recess type H or Z	St case-hard.	ZP NP Cr	A2 A4	
		tapping screws with scrape point	St case-hard.	ZP NP Cr	A2 A4	
		tapping screws for caps (article 88981/88003)	St case-hard.	ZP NP Cr	A2 A4	
DIN 7984		hexagon socket head cap screws with low head	8.8 10.9	ZP NP Cr	A2 A4	
"ISR" (ISO 14580)		hexalobular socket head cap screws, low head, (~TORX)	8.8 10.9 12.9	ZP	A2 A4	
		hexagon socket head cap screws with flange and lock ribs (article 88912)	100 12.9	ZP		
DIN 7985 (ISO 7045**)		pan head screws with cross recess	4.8 5.8 8.8	ZP NP Cr	A2 A4	Br
"ISR" (ISO 14583**)		pan head screws with hexalobular socket (~TORX)	4.8 8.8	ZP NP Cr	A2 A4	
DIN 7989-1 DIN 7989-2		washers for steel structures product grade C/product grade A	St 100 HV	ZP HDG	A2 A4	
DIN 7990		hexagon head bolts for steel structures	4.6 5.6	ZP HDG		
DIN 7991 (→ISO 10642)		hexagon socket countersunk head screws	8.8 10.9	ZP flZn	A2 A4	Br

\* DIN: ISO/EN identical = interchangeable  
 \*\* DIN: ISO/EN mostly interchangeable  
 \*\*\* standard conversion DIN : ISO  
 (→ Technical Information page 62)

① DIN standard withdrawn without replacement

Driving features:  
 H = cross recess Phillips  
 Z = cross recess pozidriv  
 ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
-------------	--------------	-----------------	----------------------------



## Standardised Products

			steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
„ISR“ (ISO 14581) (→ISO 10642 „ISR“)		hexalobular socket countersunk head screws (~TORX)	8.8 10.9 12.9	ZP flZn	A2 A4	
DIN 7992		tee head bolts with large head	3.6 4.6	ZP HDG		
DIN 7993		snap rings for shafts and bores	SSt			
DIN 7995 DIN 7996 DIN 7997		wood screws with cross recess H, – raised countersunk head – round head – countersunk head	St	ZP NP Cr	A2 A4	Br Cu Al
DIN 7999 (→EN 14399-8)		hexagon fit bolts with large head for high-strength structural bolting (HVP screws)	10.9 (12.9)	HDG		
DIN 8035 DIN 8039		hammer drills (article 88997), masonry drills (article 88990)	St hard.			
DIN 8140		wire thread inserts: coarse thread, fine pitch thread, with locking (article 88330-88346)			A2 Nimonic Inconel	bronze
		assortment wire thread inserts (article 88340, 88342)			A2	
ISO 8673*** (DIN 934)		hexagon nuts, ISO type 1, metric fine pitch thread	6 8 10	ZP NP	A1-A5	Br Cu-alloy
ISO 8674		hexagon nuts, ISO type 2, metric fine pitch thread	8 10 12	ZP NP	A1-A5	Br Cu-alloy
ISO 8675*** (DIN 439)		hexagon thin nuts with chamfers, metric fine pitch thread	04 05	ZP NP	A1-A5	Br Cu-alloy
ISO 8676*/** (DIN 961)		hexagon head screws with thread up to head, metric fine pitch thread	5.6 8.8 10.9	ZP	A1-A5	
ISO 8733 (DIN 7979)		parallel pins with internal thread	St un-tempered hard.		A1-A5 C1	
ISO 8734* (→DIN 6325)		parallel pins	St hard.		C1	
ISO 8735* (→DIN 7979)		parallel pins with internal thread	St. un-tempered		A1-A5 C1	
ISO 8736* (→DIN 7978)		taper pins with internal thread	St			
ISO 8737* (→DIN 7977)		taper pins with external thread, constant threaded part	St			
ISO 8738* (→DIN 1440)		washers for clevis pins	St	ZP NP	A1-A5	Br
ISO 8739 (→ DIN 1470)		parallel grooved pins with pilot	St	ZP NP	A1 A2 1.4104	Br Al plastic
ISO 8740** (→DIN 1473)		full length parallel grooved pins with chamfer	St	ZP NP	A1 A2 1.4104	Br Al plastic

\* DIN: ISO/EN identical = interchangeable  
 \*\* DIN: ISO/EN mostly interchangeable  
 \*\*\* standard conversion DIN : ISO  
 (→ Technical Information page 62)

① DIN standard withdrawn  
without replacement

Driving features:  
H = cross recess Phillips  
Z = cross recess pozidriv  
ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
-------------	--------------	-----------------	----------------------------



## Standardised Products

	steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
ISO 8741** (→ DIN 1474)		grooved pins, half length reverse grooved	St ZP NP A1 A2 1.4104	Br Al plastic
ISO 8742** (→ DIN 1475)		grooved pins, third length centre grooved	St ZP NP A1 A2 1.4104	Br Al plastic
ISO 8744** (→ DIN 1471)		grooved pins, full-length taper grooved	St ZP NP A1 A2 1.4104	Br Al plastic
ISO 8745** (→ DIN 1472)		grooved pins, half length taper grooved	St ZP NP A1 A2 1.4104	Br Al plastic
ISO 8746* (→ DIN 1476)		grooved pins with round head	St ZP NP A1 A2 1.4104	Br Al plastic
ISO 8747* (→ DIN 1477)		grooved pins with countersunk head	St ZP NP A1 A2 1.4104	Br Al plastic
ISO 8748** (→ DIN 7344)		spring-type straight pins, coiled, heavy duty	SSt 1.4310	
ISO 8750** (→ DIN 7343)		spring-type straight pins, coiled, standard duty	SSt 1.4310	
ISO 8752** (DIN 1481)		spring type straight pins, heavy duty	SSt 1.4310	
ISO 8765**/*** (→ DIN 960)		hexagon head bolts with shank, fine pitch thread	10.9 12.9 ZP A1-A5	
DIN 9021** (→ ISO 7093)		plain washers, outside diameter = 3 x d	St ZP HDG flZn A2 A4	Br plastic
DIN 9045		retaining rings	SSt	
DIN 9841 (→ ISO 7379)		cheese head screws with hexagon socket and beginning shank (shoulder screws)	10.9 12.9	
ISO 10509** (DIN 6928)		hexagon flange head tapping screws	St hard. ZP NP A2 A4	
ISO 10510** (DIN 6901)		tapping screw and washer assemblies with plain washers	St case-hard. ZP NP Cr A2 A4	
ISO 10511** (→ DIN 985)		prevailing torque type hexagon thin nuts, non metal (plastic ring),	04 05 ZP NP	
ISO 10512** (→ DIN 982/6924)		prevailing torque type hexagon nuts, ISO type 1, metric fine pitch thread, non metal (plastic ring)	6 8 10 ZP flZn NP Cr	
ISO 10513*** (→ DIN 980/6925)		prevailing torque type hexagon nuts, ISO type 2, metric fine pitch thread, all metal	8 10 12 ZP flZn NP Cr	
ISO 10642** (DIN 7991)		hexagon socket countersunk head screws	8.8 10.9 12.9 ZP fglZn A2 A4	Br
„ISR“		countersunk head screws with hexalobular socket (~TORX)	8.8 10.9 12.9 ZP flZn A2 A4	
ISO 10644** (DIN 6900)		screw and washer assemblies with plain washers	4.8- 10.9 12.9 ZP NP A2 A4	Br

\* DIN: ISO/EN identical = interchangeable  
 \*\* DIN: ISO/EN mostly interchangeable  
 \*\*\* standard conversion DIN : ISO  
 (→ Technical Information page 62)

① DIN standard withdrawn without replacement

Driving features:  
 H = cross recess Phillips  
 Z = cross recess pozidriv  
 ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
-------------	--------------	-----------------	----------------------------



## Standardised Products

DIN/ISO/EN	Image	Description	steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
ISO 10669		plain washers for tapping screw and washer assemblies	St	ZP NP	A2 A4	Br
ISO 10673** (DIN 6903/ 6902)		plain washers for screw and washer assemblies				
DIN 11014		flat countersunk double-nib bolts	3.6 4.6	ZP		
DIN 11015		cup head square neck bolts for agricultural machines	8.8 10.9	ZP		
DIN 11023		linch pins	St	ZP		
		pipe lynch pins (article 88023)	St	ZP		
DIN 11024		spring cotters for a bolt	St	ZP		
ISO 13337 (DIN 7346*)		spring-type straight pins, slotted, light duty	SSt			1.4310
EN 14218 (ISO 10663) (DIN 6923)		hexagon flange nuts, metric fine pitch thread	8 10 12	ZP NP	A2 A4	
		hexagon locking nuts with flange	8 10 12	ZP NP	A2 A4	
EN 14219 (ISO 15072) (DIN 6921)		hexagon nuts with flange, metric fine pitch thread	8.8 10.9 12.9	ZP flZn	A2 A4	
EN 14399 -4/-6 (DIN 6914- 6916)		assemblies of hexagon bolts, nuts and washers for high-strength structural bolting, system HV	8.8 10.9 8/10	ZP HDG		
		safety sleeves for high strength structural bolting screws (article 88916)	St			
EN 14399-8 (DIN 7999)		hexagon fit bolts with large head for high-strength structural bolting, system HV (HVP bolts)	10.9	HDG		
EN 14399-9		direct tension indicators for bolt and nut assemblies for high-strength structural bolting assemblies	St hard.	SherardZn		
EN 14399-10		bolt and nut assemblies with calibrated preload, system HRC	10.9	HDG		
ISO 14579* (→DIN 912 ISR)		hexalobular socket head cap screws (~TORX)	8.8 10.9 12.9	ZP flZn NP	A2 A4	
ISO 14580* (→DIN 7984 ISR)		hexalobular socket cheese head screws (~TORX)	4.8 5.8	ZP flZn Cr	A2 A4	
ISO 14581** (→ DIN 10642 „ISR“)		hexalobular socket countersunk head screws (~TORX)	4.8 5.8	ZP flZn Cr	A2 A4	
ISO 14583 (→DIN 7985 ISR)		hexalobular socket pan head screws (~TORX)	4.8 5.8	ZP flZn Cr	A2 A4	
ISO 14584		hexalobular socket raised countersunk head screws (~TORX)	4.8 5.8	ZP NP Cr	A2 A4	
ISO 14585 (→DIN 7981 ISR)		hexalobular socket pan head tapping screws (~TORX)	St case-hard.	ZP NP Cr	A2 A4	

\* DIN: ISO/EN identical = interchangeable  
 \*\* DIN: ISO/EN mostly interchangeable  
 \*\*\* standard conversion DIN : ISO  
 (→ Technical Information page 62)

① DIN standard withdrawn without replacement

Driving features:  
 H = cross recess Phillips  
 Z = cross recess pozidriv  
 ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
St	ZP	A2 A4	Br
case-hard.	ZP NP Cr	A2 A4	



## Standardised Products

		steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic	
ISO 14586 (→ DIN 7982 ISR)		hexalobular socket countersunk head tapping screws ( $\leq 90^\circ$ ) (~TORX)	St case-hard.	ZP NP Cr	A2 A4	
ISO 14587		hexalobular socket raised countersunk head tapping screws (~TORX)	St case-hard.	ZP NP Cr	A2 A4	
DIN 15058		axle holders (for lifting appliances)	St	ZP		
DIN 15237		seating screws with cupped washer, for attachment of components to belts	3.6	ZP	A2 A4	
ISO 15480-15483 (→ DIN 7504)		drilling screws with tapping screw thread	St case-hard.	ZP NP		
ISO 15973-16858 (DIN 7337)		blind rivets → article 88401-88488 → <b>REYHER® FIXING SYSTEMS</b>	St	ZP painted	A2 A4	Al Cu Cu-alloy plastic
DIN 16903		insert nuts for plastic mouldings	St	ZP		Br Al
DIN 18182		dry wall screws for gypsum plasterboards	St case-hard.	ZP browned		
		dry wall screws magazine				
ISO 21269 (DIN 912)		hexagon socket head cap screws with metric fine pitch thread	8.8 10.9 12.9	ZP NP	A2	
DIN 21346		square head bolts for wooden shaft guides	3.6	ZP		
DIN 21530 DIN 21547		round head bolts with oval shoulders	4.6	ZP HDG		
DIN 22424 DIN 22425		triangle head bolts	5.8	ZP NP	A1 A2	Br
DIN 25192		T-head bolts for railway vehicles	3.6 4.6	ZP		
DIN 25193		mushroom head anchor screws	3.6 4.6	ZP		
		joint shims for bolts DIN 603 (article 88102)	St	ZP		
DIN 25195		countersunk bolts with double nib	4.6	ZP		
DIN 25197		cap bolts for railway vehicles	4.6 5.8	ZP		
DIN 25200 DIN 25201 DIN 25203		bolts, nuts and safety elements for railway vehicles	4.6 8.8 10.9 St/SSt	ZP HDG flZn	A1-A5	
DIN 26020		tommy nuts for domes at tank wagons	5	ZP flZn		
DIN 28030		bolts and nuts for flange joints for vessels and process apparatuses, for the use acc. to AD-/TRD regulations	material acc. to DIN 267-13,29	ZP HDG flZn		

\* DIN: ISO/EN identical = interchangeable  
\*\* DIN: ISO/EN mostly interchangeable  
\*\*\* standard conversion DIN : ISO  
(→ Technical Information page 62)

① DIN standard withdrawn without replacement

Driving features:  
H = cross recess Phillips  
Z = cross recess pozidriv  
ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
-------------	--------------	-----------------	----------------------------



## Standardised Products

		steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
DIN 28129		St	ZP flZn		
DIN 28152		St	ZP	A4 1.7709	
DIN 32500 DIN 32501		St 4.8		A2	CuZP Al AIMg AISI
DIN 34800 DIN 34801		8.8 10.9	ZP flZn	A2 A4	
DIN 34802		8.8 10.9	ZP flZn		
DIN 34810					plastic
DIN 34811					plastic
DIN 34812					plastic
DIN 34813					plastic
DIN 34814					plastic
DIN 34815					plastic
DIN 34816					plastic
DIN 34817		8.8			
DIN 34818		SSt	flZn		
DIN 34819		St case-hard.	ZP NP	A2 A4	
DIN 34820		St 300 HV	HDG		
DIN 34821 DIN 34822 DIN 34824		8.8 10.9	ZP	A2 A4	
DIN 46258 DIN 46320		St	NP		brass
DIN 46288		SSt	ZP		
DIN 58450		St		A1	brass
DIN 70613- DIN 70618		8.8 10.9 8	ZP NP		
DIN 70852		St			

\* DIN: ISO/EN identical = interchangeable  
\*\* DIN: ISO/EN mostly interchangeable  
\*\*\* standard conversion DIN : ISO  
(→ Technical Information page 62)

① DIN standard withdrawn without replacement

Driving features:  
H = cross recess Phillips  
Z = cross recess pozidriv  
ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
-------------	--------------	-----------------	----------------------------



## Standardised Products

		steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
DIN 70951		SSt wire			
DIN 70952		St			
DIN 71412		5.8	ZP	A2 A4	
					plastic
DIN 71752		St	ZP phos		
		St	ZP		
DIN 71802		St	ZP		
DIN 71803		8.8 10.9			
DIN 71805		8 10	ZP flZn		
DIN 74361		SSt St	ZP flZn		
DIN 80403		St	ZP	A2 A4	
DIN 80701		St	ZP	A2 A4	Br
DIN 80704				A2 A4	Br Al
DIN 80705		14 H	ZP		Br
DIN 81698					Br Al
DIN 82006 DIN 82008 DIN 82010		St C 15 C 22	ZP HDG		
DIN 82013		6 Au 8	ZP	1.3952	
DIN 82024 DIN 82025 (ISO 8146)		St	ZP HDG		
DIN 82101 DIN 82102 DIN 82103		St	ZP HDG	A2 A4	
DIN 87721		St 52-3		1.4436 1.4571	

\* DIN: ISO/EN identical = interchangeable  
\*\* DIN: ISO/EN mostly interchangeable  
\*\*\* standard conversion DIN : ISO  
(→ Technical Information page 62)

① DIN standard withdrawn without replacement

Driving features:  
H = cross recess Phillips  
Z = cross recess pozidriv  
ISR/TORX = hexalobular socket

steel plain	steel coated	stainless steel	brass Cu / Al / Ti plastic
-------------	--------------	-----------------	----------------------------